ADVANCE TABCO.

HAND SINKS

ELECTRONIC OPERATED FAUCETS



Conforms To NSF 61/9 Lead Free Requirements









7-PS-51







7-PS-81

7-PS-52





7-PS-131

Item #:__ Qtv #: _ Model #: Project #: _

FEATURES:

One piece Deep Drawn sink bowl design.

Sink bowl is 10"x14"x5" (Excludes 7-PS-53. Unit has 9"x9"x5" bowl).

"Hands Free" Electronic Faucet makes use of infrared technology to sense the user's presence and immediately turn on water supply that is pre-mixed to desired temp.

Electronic gooseneck faucet is splash mounted and comes complete with AC/DC control module, sensor, 4 "AA" batteries and spout.

All sink bowls have a large liberal radii with a minimum dimension of 2" and are rectangular in design for increased capacity.

Stainless steel basket drain 1 1/2" IPS.

Additional Features:

7-PS-51 & 7-PS-81 lever operated drain and built-in overflow with plastic overflow tube and spring clamps. P-Trap is 1 1/2".

7-PS-81 towel dispenser with hinged towel box. Unit uses standard C-fold towels. Liquid Soap dispenser.

7-PS-52 towel dispenser with hinged towel box. Unit uses standard C-fold towels. Liquid soap dispenser. (Unit does not include overflow, lever drain & P-trap).

7-PS-91 pedestal skirt.

7-PS-131 K-175 electronic faucet, splash mount touchless liquid soap dispenser. 7-3/4" Side Splashes.

CONSTRUCTION:

All TIG welded

Welded areas blended to match adjacent surfaces & to a satin finish. Die formed Countertop Edge with a 3/8" No-Drip offset.

One sheet of stainless steel - No Seams.

MATERIAL:

Heavy gauge type 304 series stainless steel.

Electronic Faucet solid brass, chrome plated.

Wall mounting bracket is stainless steel and of offset design.

All fittings are brass / chrome plated unless otherwise indicated.

MECHANICAL:

Electronic faucet is 1/2" male IPS thread.

K-175 Replacement Electronic Operated Faucet.

Faucet Flow Rate: 2.2 GPM/8.3 LPM aerator, 60 PSI.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

HANDS-FREE TOUCHLESS SOAP DISPENSER UPGRADE

- · Wall Mounted
- A/C or Battery Powered (Requires 4 "AA" Batteries. Not Included)
- Low Soap Indicator Window
- Includes Wall Bracket & Hardware
- · Uses Liquid Soap

(Excludes 7-PS-131)



🔨 WARNING: Equipment that includes a faucet may expose you to chemicals, including lead, that are known to the State of California to cause cancer or birth defects or other reproductive harm. For more Info., visit www.p65warnings.ca.gov.



7-PS-91

For Orders & Customer Service: Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

DIMENSIONS and SPECIFICATIONS

FITTINGS SUPPLIED AS SHOWN TOL Overall: ± .500" Interior: ± .250" **ALL DIMENSIONS ARE TYPICAL** 7-PS-51 7-PS-61 17 1/4" 17 1/4" 15 1/4" 10" 15 1/4' Electronic Faucet Electronic Faucet 13" 5' 8" lo 13' -8<u>5</u>" Lever Drain P-Trap Basket Drain 21 lbs. 19 lbs. 7-PS-53 7-PS-81/7-PS-52 (7-PS-52 Excludes P-Trap, lever Drain & Overflow) 15 1/4" Towel Dispenser Soap Dispenser Electromic Faucet Electronic Faucet 26 1/2" (b) 13" Lever Drain 32 lbs. 12 lbs. 7-PS-91 17 1/4" ┌2" 7-PS-131 15 1/4" 15 1/4" Electronic Faucet 17 1/4" Electronic Soap Dispenser Œ Towel Dispenser Sidesplash On Both Sides 42" 37 1/2" Electronic 34" 26 1/2" Faucet

30 lbs.



Pedestal Base

41 lbs.