

ONE STATION A.D.A. FLOOR MOUNTED SQUARE CORNER SINK WITH TUBULAR LEGS & CROSS BRACING

WITH/WITHOUT MANUAL FAUCETS



8 1/2" high backsplash.

5" sink bowl depth.

Two stainless steel "Z" brackets.

One K-6 3 1/2" rear basket drain.

Tubular stainless steel legs with flanged feet.

Side & rear adjustable cross-bracing with leg clamps.

Manual Operated: Faucets sold separately.

"-F" Series includes one K-161-LU 6" gooseneck faucet with Wrist Handles.

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.



"-F" Series Sink Includes K-161-LU Gooseneck Faucets with Wrist Handles

ltem #:	Qty #:
Model #:	
Project #:	







MATERIAL:

All 16 GAUGE type "304" stainless steel.

1 5/8" tubular "304" stainless steel legs & cross-bracing. Stainless steel gussets.

MECHANICAL:

8" O.C. faucet holes punched at each station.

		# of Faucets Sink	# of Faucets		Cu.
Model #	Length	Accommodates	Included	Wt.	Ft.
19-FM-1-ADA	40"	1	0	62 lbs.	15
			(Faucets Not Included)		
19-FM-1-ADA-F	40"	1	1	64 lbs.	15
			(K-161-LU Faucet Included)		

Click Here For Install Guide



Ships UPS

Standard Faucets conform to NSF 61 Standard 9 and compliance to AB 1953 Standards.

MARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

DETAILS and SPECIFICATIONS

TOL ± .500" FITTINGS SUPPLIED AS SHOWN ALL DIMENSIONS ARE TYPICAL



