

P120E "C" Modular electric oven for pizzeria

COMPOSITION WITH 1 BAKING CHAMBER



OPTIONS AND ACCESSORIES (WITH SURCHARGE)

- Leavening prover on wheels, height 800mm (31 1/2")
- □ Support with wheels, height 600mm (23 1/2")
- □ Support with wheels, height 800mm (31 1/2")
- □ Support with wheels, height 950mm (37 1/2")
- Additional tray holder guides for compartment and support
- □ Spacer element height 300mm (12")
- Suction hood

(WITHOUT SURCHARGE)

□ Front vapour collection hood in stainless steel sheet

EXTERNAL CONSTRUCTION

- □ Structure made in folded stainless steel
- Given panels in pre-painted sheet metal
- □ Stainless steel hood with aluminised steel top cover
- Front vapour collection hood in HT coating steel sheet
- □ Steam duct in stainless steel plate
- □ Stainless steel double door with bottom hinge and spring balance
- Tempered glass element
- Handles in thermoplastic material
- Control panel on front right hand side

INTERNAL CONSTRUCTION

- Refractory brick cooking surface
- Aluminated steel top and side structure
- Rock wool heat insulation

FUNCTIONING

- □ Heated by armoured heating elements
- Electronic temperature management with independent adjustment of ceiling and floor
- □ Maximum temperatura reached 450°C (840°F)
- Continuous temperature monitoring with thermocouple
- □ Vapour ducting using manual butterfly valve

STANDARD EQUIPMENT

- □ Lighting with halogen lamp
- Timer
- Economiser
- Independent maximum temperature safety device
- 20 customisable programs



MORETTI FORNI S.P.A.

www.morettiforni.com info@morettiforni.com Via A.Meucci, 4 - 61037 Mondolfo (PU) ITALIA Tel. +39.0721.96161 - Fax +39.0721.9616299 7/16



P120E "C" **1 baking chamber height 18cm (7")** (assembled with support height 950mm (37 1/2"))

TOP VIEW REAR VIEW **RIGHT SIDE VIEW** ITA ACQU STEAMER WATER INFEED EE 28 869 (180 62 SCARICO VAPOR STEAM EXHAUST 0'W) 1879 (74") 195 1610 (63 1/2") 1680 C C ABLAGGIO ELET LECTRIC WIRING 1547 10 PASSACAV FAIRLEADS 1210 300 235 Ŧ 182 338 700 65 TENZIALE IAL SCREWS 185 NTIAL SURE ... 3/8" GAS MASCHIO/MÁLE SCARICO CONDENSA CONDENSATE EXHAUST 83 8 180 200,187 20 1243 Ø 150 (n Π 805 805 6 117 RACCOLTA VAPORI CAPPA HOOD STEAM COLLECTOR

Note: The dimensions indicated in the views are in millimeters. Steamer for Bakery only.

SPECIFICATIONS

The appliance comprises one cooking element and an optional leavening compartment or support. The oven cooking surface is made of refractory, allowing pefect heat distribution over the whole surface and making this oven particularly suitable for use by pizza cooks. Temperature adjustment is electronic, with independent control of the ceiling and floor heating elements. The oven door is hinged at the bottom, with a tempered glass window to check the state of the product while it is cooking. The support comprises a painted metal structure, whereas the leavening compartment has a stainless steel structure and is fitted with a heating thermostat. The leavening compartment can reach a maximum temperature of 65°C (150°F), whereas the maximum temperature of the baking chamber is 450°C (840°F)

All the data provided below refer to the configuration with 1 baking chamber

DIMENSIONS

SHIPPING INFORMATION

FEEDING AND POWER

External height External depth External width Weight Baking surface	1700mm (67") 1879mm (74") 1610mm (63 1/2") 346kg (763lb)) 1,6m² (17,22ft²)	Height Depth Width	900mm (36") 2052mm (81")	Standard feeding A.C. V240 3ph Feeding on request A.C. V208 3ph Frequency Max power	60Hz 17kW
TOTAL BAKING CAPACITY		When combined compartment or s	0	*Average power cons Ampère Max	8,5kWh
Tray (600x400)mm 6		Max height	1850mm (73")		
Tray 26"x18" 4			(518)kg (1142)lb		
Pizza diameter 300mm (12") 8		-		Connecting cable	
Pizza diameter 450mm (18") 6				(6AWG)	
				Power supply (optional prover) A.C. V(208/240) 1ph 60 Hz	
				Max power Average power cons Conn. Cable (14AWG)	1,8kW 0,9kWh

* This value is subject to variation according to the way in which the equipment is used

- NOTE: MORETTI FORNI S.P.A. reserves the right to modify the characteristics of the products illustrated in this publication without prior notice