

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

P-SERIES TOP MOUNT FREEZER

PF1HC-1BHG Half-Glass Door Reach-In Hydrocarbon Series

MODEL: PF1HC-1BHG



3 Year Parts/Labor Warranty Additional 4 Year Compressor Warranty

CABINET CONSTRUCTION

- Exterior stainless steel front and side (galvanized top, bottom & back)
- · Interior is made of corrosion resistant aluminum
- Full electronic control
- · Expansion valve technology
- · Self-closing doors with 120° stay-open feature
- · Half-glass door
- · LED interior light
- · Cylinder locks
- · Snap-in magnetic gaskets for positive door seal
- · Low profile vertical door handles
- · Hinged front shroud
- Energy saving thermal breaker
- · Stainless steel breaker caps
- · 3 Heavy-duty epoxy wire coated shelves
- · 6" High adjustable stainless steel legs
- 8' Cord and plug (see electrical data for details)

OPTIONS & ACCESSORIES

- · Stainless steel case back
- · Stainless steel interior
- Additional shelves
- 3" or 6" casters
- · 6" Seismic legs
- Tray slides (type A & A/C)
- · Door swing orientation (at time of order)
- · Remote option (see note back on page)

REFRIGERATION SYSTEM

- · Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- · Adaptive defrost
- · Epoxy coated evaporator coil, located out of the food zone
- Freezer capable of maintaining product temperature down to -10°F




















MODEL	PF1HC-1BHG
EXTERNAL DIMENSIONAL DATA	
Width Overall	26 ½"
Depth Overall with Handle	33 ¾"
Height Overall	84 1⁄8"
Number of Doors	2
Depth with Door Open 90°	57 ¾"
Door Opening (in)	21 ½" x 25 ¼"
INTERNAL DIMENSIONAL DATA	
NET Capacity (cubic ft.)	21.01
Internal Width Overall (in)	22 ½"
Internal Depth Overall (in)	26"
Internal Height Overall (in)	56 %"
No. of Shelves	3
ELECTRICAL DATA	
Full Load Amperes 115/60/1*	9.1
REFRIGERATION DATA	
Horsepower	3/4
Capacity (BTU/Hr)	2450
SHIPPING DATA	
Gross Weight (crated lbs)	398 lbs
Height - Crated	87"
Width - Crated	45"
Depth - Crated	35"

NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

Top Mount Freezer Model: PF1HC-1BHG



ELECTRICAL CONNECTION



Unit pre-wired at factory and include 8' long cord and plug

 * NOTE: This unit utilizes variable speed compressor technology. The compressor can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 mA to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Beverage-Air recommends using a HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle















