# C500 ESPRESSO System

0.0" x 0.0" x 0.0" (0.0cm x 0.0cm x 0.0cm)



- Variable Bypass Head
- Specialized blend of resin targeted to reduce hardness and alkalinity
- · Designed specifically for espresso applications
- 100% treatment of the water including the bypass to reduce taste and odor
- System maximum operating pressure is 125psi (862kPa) and operating temprature 100 degrees F (38C)
- · Includes water test kit
- Can be mounted in vertical or horizontal positions
- C500 provides 1796gal (6798L) of hardness reduction @10GPG (grains per gallon)

Agency:



#### **Specifications**

Product #: 47152.0000

Cartridge Type: Quick Change

#### **Additional Features**

#### Capacity

Service Flow Rate	Capacity	Micron Rating
_	1796 gal. (6798.5 L)	-
	@10 GPG of hardness	

### Plumbing Requirements

Max Operating Pressure			Outlet Connection	
<u>-</u>	-	-	-	



Unit			Shipping					
	Width	Height	Depth	Width	Height	Depth	Weight	Volume
English	-	-	-	-	-	-	7.000 lbs	-
Metric	-	-	-	-	-	-	3.175 kgs	-



## Related Products & Accessories: C500 ESPRESSO System(47152.0000)





