

Angle Guide Racks

Aluminum

JOB_____ ITEM # _____ QTY # _____



MODEL NUMBER

DXPA3618269
DXP2A72182640
DXPA60182610
DXPA60182616
DXPA3618265
DXPA72182612
DXPA72182620
DXPA4818268
DXP2A72182624

DIMENSIONS

MODEL NO.	DIMENSIONS WDH	CLEAR SPACING	CAPACITY 18" x 26" PANS	WEIGHT
DXPA3618269	201/2" x 26" x 36"	3"	9	62
DXPA60182616	201/2" x 26" x 60"	3"	16	70
DXPA72182620	201/2" x 26" x 72"	3"	20	75
DXP2A72182640	40" x 26" x 72"	3"	40	170
DXPA3618265	201/2" x 26" x 36"	5"	5	58
DXPA4818268	201/2" x 26" x 48"	5"	8	62
DXPA60182610	201/2" x 26" x 60"	5"	10	66
DXPA72182612	201/2" x 26" x 72"	5"	12	70
DXP2A72182624	40" x 26" x 72"	5"	24	140

 $Capacity: Last \ digits \ of model number indicate the quantity of 18"x 26" pans per rack.$

RACKS OPTIONS / ACCESSORIES PART NUMBER

Option	Description	
DXPPS	Pan Stop	
DXPEMB	Personalized Embossment (12 letters per line)	
DXPFL	Floor Lock (REQUIRES SB OPTION)	
DXPPH	Push Handle	
DXPY5	5" Polyurethane Casters (set of 4)	
DXPB	Non-Marking Rubber Bumpers - Corner (set of 4) (REQUIRES SB OPTION)	
DXPPB	Non-Marking Rubber Bumpers - Full Perimeter (REQUIRES SB OPTION)	
DXPWB	Wheel Brakes (set of 2)	
DXP52	Heavy-duty Casters (set of 4) (REQUIRES SB OPTION)	
DXPV	Vertical Bumpers	
DXPSB	Solid Bottom	
DXPR	Rotating Bumper (ONLY ON UNITS WITHOUT SB OPTION)	

SPECIFICATIONS

Series DXPA, heavy duty, aluminum angle guide, open racks for 18" x 26" sheet pans. (Optional for two 14 x 18 trays)

FRAME

The vertical uprights and the top and bottom cross bracing are 2" x 1" x 1/8" thick extruded aluminum channels welded to form a rigid frame.

GUIDES

The guides are 1" x 11/2" x .100" thick extruded aluminum angles welded to the vertical uprights, with all corners chamfered and deburred.

TIE ROD

Models DXPA60, DXPA72 and DXP2A72 have 1/2" diameter aluminum tie rods welded to the front and rear vertical uprights for extra rigidity.

CASTERS

The units are mounted on four 5" diameter, heavy duty, swivel casters.

LIMITED WARRANTY: DINEX warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may not bear the appropriate labels at all times.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.



4711 E. Hefner Road Oklahoma City, OK 73131 800.654.8210 405.475.5600

We do not accept returns on any Dinex equipment or Dinex custom products. Please contact your local Dinex rep to ensure order accuracy prior to ordering.