



Profit from the Eagle Advantage®

# Specification Sheet

## Short Form Specifications

Eagle Stem Caster, model \_\_\_\_\_. For use with 1"-diameter posts. Resilient or polyurethane tread. Casters with zinc, stainless steel, and polymer boot available. For electronic handling, conductive casters available. Donut bumper included with all stem casters. Swivel casters have a temperature rating of -15°F (-26°C). Note: These stem casters cannot be used with Master Trak® Shelving.

Item No.: \_\_\_\_\_  
 Project No.: \_\_\_\_\_  
 S.I.S. No.: \_\_\_\_\_

## Stem Casters

### MODELS:

- |                                   |                                   |                                    |                                  |
|-----------------------------------|-----------------------------------|------------------------------------|----------------------------------|
| <input type="checkbox"/> CSS4-125 | <input type="checkbox"/> CSB5P-*  | <input type="checkbox"/> CSPB5-300 | <input type="checkbox"/> A201008 |
| <input type="checkbox"/> CSS5-*   | <input type="checkbox"/> CSR5P-*  | <input type="checkbox"/> CPSS5PS-* | <input type="checkbox"/> A201009 |
| <input type="checkbox"/> CSB5-*   | <input type="checkbox"/> CSS5PS-* | <input type="checkbox"/> CPSB5PS-* | <input type="checkbox"/> A204795 |
| <input type="checkbox"/> CSR5-*   | <input type="checkbox"/> CSB5PS-* | <input type="checkbox"/> A201706   | <input type="checkbox"/> A207562 |
| <input type="checkbox"/> CSS5P-*  | <input type="checkbox"/> CSR5PS-* | <input type="checkbox"/> A201007   | <input type="checkbox"/> A200019 |
|                                   |                                   |                                    | <input type="checkbox"/> A213261 |

\* See charts for complete model numbers.



### Casters with Resilient Tread

type	EAGLEbrite® zinc capacity			stainless steel capacity			wheel diameter		wheel face		weight	
	model #	lbs.	kg	model #	lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CSS4-125	125	56.7	n/a			4"	102	1"	25	1.1	0.5
swivel	CSS5-125	125	56.7	n/a			5"	127	1"	25	2.0	0.9
swivel	CSS5-300	300	136.1	CSS5S-300	300	136.1	5"	127	1 1/4"	32	2.5	1.2
w/brake	CSB5-300	300	136.1	CSB5S-300	300	136.1	5"	127	1 1/4"	32	2.8	1.3
w/step-pedal brake	CSPB5-300	300	136.1	n/a			5"	127	1 1/4"	32	2.8	1.3
rigid ▼	CSR5-300	300	136.1	CSR5S-300	300	136.1	5"	127	1 1/4"	32	3.5	1.6



### Casters with Polyurethane Tread

type	nickel-plated model #	stainless steel capacity		wheel diameter		wheel face		weight		
		model #	lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CSS5P-300	CSS5PS-300	300	136.1	5"	127	1 1/4"	32	2.5	1.1
w/brake	CSB5P-300	CSB5PS-300	300	136.1	5"	127	1 1/4"	32	2.8	1.3
rigid ▼	CSR5P-300	CSR5PS-300	300	136.1	5"	127	1 1/4"	32	3.5	1.6



### Conductive Casters For electronic handling only.

type	EAGLEbrite® zinc capacity		wheel diameter		wheel face		weight		
	model #	lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	CSS5-CC	200	90.7	5"	127	1 1/4"	32	2.5	1.1
w/brake	CSB5-CC	200	90.7	5"	127	1 1/4"	32	2.8	1.3
rigid ▼	CSR5-CC	200	90.7	5"	127	1 1/4"	32	3.5	1.6

▼ See back page for optional Channel Frames available for use with rigid casters.

**EAGLE GROUP**  
 100 Industrial Boulevard, Clayton, DE 19938-8903 USA  
 Phone: 302-653-3000 • Fax: 302-653-2065  
 www.eaglegrp.com

**Foodservice Division: Phone 800-441-8440**  
**MHC/Retail Display Divisions: Phone 800-637-5100**

For custom configuration or fabrication needs, contact our **SpecFAB® Division**.  
 Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

### Certifications / Approvals



EG01.05A Rev. 04/18

**Spec sheets available for viewing, printing or downloading from our online literature library at [www.eaglegrp.com](http://www.eaglegrp.com)**

Eagle Foodservice Equipment, Eagle MHC, SpecFAB®, and Retail Display are divisions of Eagle Group. ©2018 by the Eagle Group



Profit from the Eagle Advantage®

Item No.: \_\_\_\_\_  
 Project No.: \_\_\_\_\_  
 S.I.S. No.: \_\_\_\_\_

## Stem Casters



cart-washable  
caster

### Cart-Washable Casters

Features stainless steel boot, swivel stem, sealed precision bearings, and polyurethane wheel.

type	stainless steel model #	capacity		wheel diameter		wheel face		weight	
		lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>CSS5WPS-300</b>	300	136.1	5"	127	1 1/4"	32	2.0	0.9
brake	<b>CSB5WPS-300</b>	300	136.1	5"	127	1 1/4"	32	2.0	0.9




polymer caster

### Polymer Casters

With polyurethane tread.

type	model #	type of bearing	capacity		wheel diameter		wheel face		weight	
			lbs.	kg	in.	mm	in.	mm	lbs.	kg
swivel	<b>CPSS5-250</b>	delrin	250	113.4	5"	127	1 1/4"	32	2.0	0.9
brake	<b>CPSB5-250</b>	delrin	250	113.4	5"	127	1 1/4"	32	2.0	0.9



channel frame

### Channel Frames—for Rigid Stem Casters

Please note that shelf width must be known when ordering rigid stem casters in order to ship appropriate channel frame to lock rigid casters.

model #	shelf width		weight	
	in.	mm	lbs.	kg
<b>A201706</b>	14"	356	1.5	0.7
<b>A201007</b>	18"	457	2.0	0.9
<b>A201008</b>	21"	533	2.5	1.1
<b>A201009</b>	24"	610	2.8	1.3
<b>A204795</b>	30"	762	3.5	1.6
<b>A207562</b>	36"	914	4.0	1.8



donut bumper  
#A200019

### Donut Bumpers—for all Stem Casters

description	model #
3 1/2" (89mm) diameter	<b>A200019</b>
5" (127mm) diameter, with swivel center	<b>A213261</b>

### EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A.  
©2018 by Eagle Group

Rev. 04/18

Spec sheets available for viewing, printing or downloading from our online literature library at [www.eaglegrp.com](http://www.eaglegrp.com)

Although every attempt has been made to ensure the accuracy of the information provided, we cannot be held responsible for typographical or printing errors. Information and specifications are subject to change without notice. Please confirm at time of order.