

| ltem # | | |
|--------|--|--|
| | | |
| | | |
| Joh | | |



STAINLESS STEEL Wire Shelving

- Design: The open wire design of these heavy gauge stainless steel coated shelves minimizes dust accumulation and allows a free circulation of air, greater visibility of stored items and greater light penetration.
- Versatile: Our shelves can change as quickly as your needs change. By using various sizes, hundreds of shelving configurations become possible.
- Fast and Secure Assembly: Posts with the double groove visual guide feature, have circular grooves at I" (25mm) intervals and are numbered at 2" (50mm) intervals. A tapered split sleeve (plastic) snaps together around each post. Tapered openings in the shelf corners slide over the tapered split sleeves to lock on the shelf. Shelf is assembled in minutes without the use of any special tools.
- **Shelf Ribs:** Run front to back, allowing you to slide items on and off shelves smoothly.
- **Shelf Accessibility:** Shelves can be adjusted at I" (25mm) intervals along the entire length of the post.
- **Durable:** Constructed of 201 stainless steel wire.
- Adjustable Feet: Bolt levelers compensate for uneven surfaces.
- **Strength:** Each shelf up to 48" in length is rated to support up to 800 lbs. of uniformly distributed weight. Shelves longer than 48" support 600 lbs.

Wire Shelves



| Item No. | Description | Width | | Length | | Weight/pc |
|--------------|--------------|-------|------|--------|------|-----------|
| Wire Shelves | (in) | (in) | (mm) | (in) | (mm) | (lbs.) |
| FF1824WRSS | 18X24, Shelf | 18 | 610 | 24 | 455 | 5.6 |
| FF1830WRSS | 18×30, Shelf | 18 | 760 | 30 | 455 | 7 |
| FF1836WRSS | 18×36, Shelf | 18 | 910 | 36 | 455 | 8.4 |
| FF1842WRSS | 18×42, Shelf | 18 | 1060 | 42 | 455 | 9.8 |
| FF1848WRSS | 18×48, Shelf | 18 | 1220 | 48 | 455 | 11.3 |
| FF1860WRSS | 18×60, Shelf | 18 | 1525 | 60 | 455 | 14.1 |
| FF1872WRSS | 18×72, Shelf | 18 | 1825 | 72 | 455 | 16.9 |
| FF2424WRSS | 24×24, Shelf | 24 | 610 | 24 | 610 | 7.5 |
| FF2430WRSS | 24×30, Shelf | 24 | 610 | 30 | 760 | 9.4 |
| FF2436WRSS | 24×36, Shelf | 24 | 610 | 36 | 910 | 11.3 |
| FF2442WRSS | 24×42, Shelf | 24 | 610 | 42 | 1060 | 13.1 |
| FF2448WRSS | 24×48, Shelf | 24 | 610 | 48 | 1220 | 15 |
| FF2460WRSS | 24×60, Shelf | 24 | 610 | 60 | 1525 | 18.8 |
| FF2472WRSS | 24X72, Shelf | 24 | 610 | 72 | 1825 | 22.5 |
| | | | | | | |

Split Sleeves



Plastic split sleeves are provided with shelf. One bag required per shelf. Packed 4 sets per package. Item No. 30058 Replacement sleeves.



Aluminum Split Posts
For high temperature, demanding or
conductive applications. Zinc retainer ring.
4 sets per bag. I set required per shelf.
Item No. FFSALSLV

"S" Hooks

Used to "add-on" shelving units with only two posts required. Item No. 93333 Chromate Item No. 93333GN Green Epoxy



Posts

Posts are grooved at 1" (25mm) increments and numbered at 2" (50mm) increments. Posts are double grooved every 8" (203mm) for easy identification.



| Item No. Epoxy | Description (in.) | He (in.) | ight (mm) | Weight/pc (lbs.) |
|-------------------|-------------------|-------------|--------------|---------------------|
| FGN063SS | Post, 63 Mobile | 63 | 1589 | 13.1 |
| FG063SS | Post, 63 w/Foot | 63 | 1589 | 13.1 |
| FGN074SS | Post, 74 Mobile | 74 | 1895 | 15.4 |
| FG074SS | Post, 74 w/Foot | 74 | 1895 | 15.4 |
| FGN086SS | Post, 86 Mobile | 86 | 2200 | 17.8 |
| FG086SS | Post, 86 w/Foot | 86 | 2200 | 17.8 |

