

PROJECT:	
ITEM #	
MODEL #	

SIS #

_ QTY: _

AIA

PASS-THRU SOLID HALF-DOOR REACH-IN FREEZER

FS-2D-S1-PT-HD-HC





- **3 Year Parts & Labor Warranty**
 - Plus An Additional 4 Year Compressor Warranty
 - Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)

OPTIONS & ACCESSORIES

- Secure-Temp[™] Technology
- Stainless Steel Case Back
- Stainless Steel Kick Plate
- Exterior Door Laminate Door Swing Orientation (at time of order)
- 3", 6" Casters Or 6" Seismic Legs

Additional Shelves

• Heat Shield (left, right)

Tray Slides (type A & A/C)

FlexTemp Models Maintain Between 0°F And 20°F

CABINET CONSTRUCTION

- Stainless Steel Exterior And Interior
- Stay-Open Door Feature For Easy Product Loading
- 20 Gauge Stainless Steel Solid Half-Door
- Magnetic Door Switch Automatically Activates Interior LED Light
- Heavy-Duty Cylinder Locks
- Stainless Steel Interior Door Liner
- One Piece, Snap-In Magnetic Door Gaskets
- Low Profile Vertical Door Handles
- Hinged Front Shroud
- Energy Saving Thermal Breaker
- Stainless Steel Breaker Caps
- 6 Silver Freeze Wire Shelves
- 6" High Adjustable Stainless Steel Legs
- 8' Cord And Plug (see electrical data for details)

FEATURES

- Full Electronic Control With Touchpoint Interface
- Expansion Valve Technology
- Manager's Lockout Feature
- Anti-Condensate Perimeter Heater
- Variable Speed Compressor Technology

REFRIGERATION


- Refrigeration System Uses R-290 Refrigerant To Comply With All **Environmental Concerns**
- Hot Gas Condensate Evaporator
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- Epoxy Coated Evaporator Coil, Located Out Of The Food Zone
- Freezer Capable Of Maintaining Product Temperature -10°F





Please verify qualifying units by visiting: www.energystar.gov/cfs

- Correctional Package
- Remote Models* (6" legs only) (refrigerant must be specified at time of order, see note)









We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

12" Top and 3" rear clearance is required

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity (cubic ft.)	48.33	Cabinet Voltage	115/60/1	Height	88″
Width, Overall (in.)	52 1/8″	Total Amperes	13.9	Width	60″
Depth, Overall (with handle)	38 5/8″	NEMA Plug (8' cord)	5-20P	Depth	45″
Height Overall (6" legs)	84 1/8"	REFRIGERATION DATA		Crated Weight	647 lbs
Depth, Door Open 90°	83 7/8"	Condensing Unit Size, HP	(2) 3/4	*NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified at	
Door Opening (in.)	21 1/2" x 25 1/4"	Refrigerant*	R-290		
No. Of Doors/Shelves	8/6	Capacity (BTU/HR) (100°F/20°F)	4900		
		Heat Rejection (BTU/HR)	7350	time of order.	
		Charge (Ibs/grams)	0.2866/130		

 3779 Champion Blvd, Winston-Salem, NC 27105
 ph: (888) 845-9800
 fax: (800) 253-5168

 Sales@VictoryRefrigeration.com
 VictoryRefrigeration.com

 Rev. 9/30/21
 Printed in U.S.A.

an Ali Group Company

