

# FOUR STATION FLOOR MOUNTED SINK WITH TUBULAR LEGS & CROSS BRACING

### **KNEE OPERATED**



#### **FEATURES:**

8 1/2" high backsplash.

8" sink bowl depth.

Two stainless steel "Z" brackets.

One K-6 3 1/2" rear basket drain.

Tubular stainless steel legs with flanged feet.

Side & rear adjustable cross-bracing with leg clamps.

**Knee Operated:** Includes four **7-PS-32** knee valves and four **K-121** spouts.

#### **CONSTRUCTION:**

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.



Knee Valves Included On All "KV" Models

Item #:	Qty #:
Model #:	
Project #:	





#### **MATERIAL:**

All 14 gauge type "304" stainless steel.

1 5/8" tubular "304" stainless steel legs & cross-bracing. Stainless steel gussets.

#### **MECHANICAL:**

Single faucet hole punch at each station.

	# of			Cu.
Model #	Length	Spouts	Wt.	Ft.
FS-FM-80KV	80"	4	160 Lbs.	28



#### **MULTI-STATION ACCESSORIES & REPLACEMENT PARTS** Model **Description** QTY: Knee Valve Assembly **7-PS-32 F** K-6 3 1/2" Drain (1 1/2" I.P.S.) **F** K-06 Splash Mount Faucet Mounting Kit Stainless Steel Soap Dispenser (Wall Mount Only) **K-13** K-411 **K-121** Single Hole, Splash Mounted 3-1/2" Gooseneck Spout Strainer Plate for 3-1/2" Drain **K-411** Special Sizing Charge (Larger Size **K-508** TA-19 Cut Down To Smaller Size) K-06 **TA-19** Adjustable Stainless Steel Flanged Bullet Foot

= Ships UPS

Standard Faucets conform to NSF 61 Standard 9 and compliance to AB 1953 Standards.

**MARNING:** Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes: Email: smartfab@advancetabco.com or Fax: 631-586-2933

## **DETAILS and SPECIFICATIONS**

TOL ± .500" ALL DIMENSIONS ARE TYPICAL



