

PROJECT:		
ITEM #		QTY:
MODEL #		
AIA #	SIS #	

EXTRA WIDE DUAL TEMP REACH-IN WARMING CABINET & REFRIGERATOR

HRSA-1D-S1-EW-HD-HC















- 3 Year Parts & Labor Warranty Plus An Additional 4 Year Compressor Warranty
- **Exclusive 2 Year Warranty On Magnetic Door Gaskets**
- Lifetime Warranty On Handles & Hinges (Parts Only)
- **OPTIONS & ACCESSORIES**
- Secure-Temp™ Technology
- Exterior Door Laminate
- · Stainless Steel Case Back
- · Additional Shelves
- · Stainless Steel Kick Plate
- Tray Slides (type A & A/C)
- · Glass Door Models
- · Door Swing Orientation (at time of order)

CABINET CONSTRUCTION

- Stainless Steel Exterior And Interior
- **Aluminum Interior**
- Stainless Steel Interior Door Liner
- Warming Cabinet On Top, Refrigerator On Bottom
- Stay-Open Door Feature For Easy Product Loading
- 20 Gauge Stainless Steel Door
- Top: Warmer, Bottom Refrigerator
- Refrigerator Has Magnetic Door Switch Automatically Activates Interior LED Light
- Warmer Has Magnetic Door Switch Automatically Activates Interior Incandescent Light
- **Heavy-Duty Cylinder Locks**
- One-Piece, Snap-In Magnetic Door Gaskets
- Low Profile Vertical Door Handles
- **Hinged Front Shroud**
- Thermal Breaker
- Stainless Steel Breaker Caps
- Six Silver Freeze Wire Shelves
- 6" High Adjustable Stainless Steel Legs
- 8' Cord And Plug (see electrical data for details)

- Full Electronic Control With Touchpoint Interface
- Expansion Valve Technology (refrigerator only)
- Insulated Partition Wall Separates Compartments

REFRIGERATION

- Refrigeration System Uses R290 Refrigerant To Comply With All **Environmental Concerns**
- Hot Gas Condensate Evaporator
- Automatic Non-Electric, Defrost
- Epoxy Coated Evaporator Coil, Located Out Of The Food Zone
- Refrigerator Capable Of Maintaining Product Temperature 36°F to 38°F

Warming Cabinet Maintains Product Temperature 80°F to 180°F



Please verify qualifying units by visiting: www.energystar.gov/cfs

- · 6" Casters 6" Seismic Legs
- Correctional Package
- Remote Models* (refrigerators & 6" legs only) (refrigerant must be specified at time of order see note on back on page)

3779 Champion Blvd, Winston-Salem, NC 27105


ph: (888) 845-9800 | fax: (800) 253-5168


Rev 8/20/20 Printed in the U.S.A.


APPROVAL: _ DATE: _



HRSA-1D-S1-EW-HD-HC







We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

12" top, 3" sides and rear clearance is required

12 top, 3 sides and real clearance is required								
CHARACTERISTICS		ELECTRICAL DATA REFRIGERATOR		SHIPPING DETAILS				
Net Capacity W/R	10.1 / 10.1	Cabinet Voltage	115/60/1	Height	87"			
Width, Overall (in.)	31 1/4"	Total Amperes	7.5	Width	57"			
Depth, Overall (with Handle)	35"	NEMA Plug* (8' cord)	5-15P	Depth	48"			
Height Overall (6" legs)	84 1/8"	REFRIGERATION DATA		Crated Weight	435 lbs			
Depth, Door Open 90°	59 1/8"	Condensing Unit Size, HP*	1/3	*NOTE: Remote unit are field wired and come with 6" legs. Refrigerant must be specified at time of order.				
Door Opening (in.)	22 7/8" x 24 3/4"	Refrigerant*	R290					
No. Of Doors / Shelves	2/4	Capacity (BTU/HR) (100°F/20°F)	Variable Speed Technology					
		ELECTRICAL DATA WARMING CABINET						
		Cabinet Voltage	230/60/1]				
		Total Amperes	3.2 /3.7	1				
		NEMA Plug* (8' cord)	6-20P]				

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Rev. 8/20/20 Printed in the U.S.A.

