



Model: \_\_\_\_\_ Item #: \_\_\_\_\_ Date: \_\_\_\_\_  
 Project: \_\_\_\_\_ Qty: \_\_\_\_\_ Approved By: \_\_\_\_\_

**Royal Series Four Compartment Bar Sink**

**Royal Series Underbar**



**OPTIONAL ACCESSORIES**

<b>KR-402</b>	Faucet Install Kit
<b>21-443L</b>	3/8" E-Z Install Wall Mount Faucet Water Line Kit
<b>KR-310</b>	Right End Splash
<b>KR-311</b>	Left End Splash
<b>KR-401</b>	Cap Catcher and Opener
<b>KR-501</b>	Towel Ring
<b>30-160</b>	Perforated Dump Basket
<b>KR-806</b>	Upgrade: 6" Longer Stainless Steel Legs
<b>RS-"XX"</b>	Sound Deadened Single Speedrail ("XX" indicates size)
<b>RD-"XX"</b>	Sound Deadened Double Speedrail ("XX" indicates size)

**STANDARD FEATURES**

<b>Sink Bowl</b>	20 gauge stainless steel. 10" x 14" x 10" deep sink bowl. Furnished with 1-1/2" IPS rear corner drain and 7-1/2" overflow pipe
<b>Drainboard</b>	20 gauge stainless steel reinforced with welded braces every 6"
<b>Front Apron</b>	20 gauge stainless steel clad over 20 gauge galvanized steel
<b>Sides</b>	20 gauge stainless steel
<b>Backsplash</b>	20 gauge stainless steel
<b>Back and Bottom</b>	20 gauge galvanized steel
<b>Legs</b>	1-5/8" tubular 16 gauge stainless steel with grey plastic bullet foot
<b>Plumbing</b>	Hot/Cold Water: 1/2" IPS Drain: 1-1/2" IPS
<b>Faucet</b>	4" OC wall or deck mount faucet with double jointed spout and ceramic cartridge valves



Conforms to NSF St. 2



Model: \_\_\_\_\_ Item #: \_\_\_\_\_ Date: \_\_\_\_\_  
 Project: \_\_\_\_\_ Qty: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Royal Series Four Compartment Bar Sink

## Royal Series Underbar

### KR19

Model Numbers	Overall Length A	Drainboard B	Left Side to Drain C	Bowl Location	Weight (lbs.)
KR19-44C	4'-0"	N/A	4"	Center	115
KR19-64C	6'-0"	12" Each	15"	Center	140
KR19-74C	7'-0"	18" Each	21"	Center	155
KR19-84C	8'-0"	24" Each	27"	Center	190

**NOTE:** Letter at end of Model Number represents Bowl Location  
**MECHANICAL REQUIREMENTS:** 1/2" IPS Hot and Cold water. 1-1/2" IPS drain connection.

### KR24

Model Numbers	Overall Length A	Drainboard B	Left Side to Drain C	Bowl Location	Weight (lbs.)
KR24-44C	4'-0"	N/A	4"	Center	125
KR24-64C	6'-0"	12" Each	15"	Center	155
KR24-74C	7'-0"	18" Each	21"	Center	170

**NOTE:** Letter at end of Model Number represents Bowl Location  
**MECHANICAL REQUIREMENTS:** 1/2" IPS Hot and Cold water. 1-1/2" IPS drain connection.



Conforms to NSF St. 2