



Consistent, repeatable results

The **HydroPro™ Plus** initiates a new generation of professional sous vide immersion circulators. Featuring **Sous Vide Toolbox™**, an intuitive on-board guided cooking experience that simplifies sous vide cooking by using scientific algorithms to calculate time to temperature and pasteurization for a vast range of foods.

The **HydroPro™ Plus** includes a digital needle probe that displays the core temperature of the food in real-time, enabling delta cooking. Data is stored on-board and can be transferred to the **HACCP Manager App** via Bluetooth for easy logging of all your sous vide cooks.

Programming and repeatability of your cooks is made simple thanks to 'My Presets' and usability has been enhanced via a large touch screen that allows easy manual input of cooking parameters. The powerful heater and newly designed pumping system ensure precise temperature control across a wide range of cooking volumes.

Designed with food safety and simple maintenance in mind, the design features a smooth waterproof construction, quick-release clamp, and a magnetic impeller for easy cleaning and descaling. Removable parts are commercial dishwasher safe.

Visit www.polyscienceculinary.com to learn about the entire line of Breville | PolyScience products and great recipe ideas.

Sous Vide Immersion Circulator

Technical Specifications

PERFORMANCE

Power	1450 Watts
Flow Rate	17 L/Min
Max Water Bath Size	45L with lid

DURABILITY

- IPX7 Water Resistant
- NSF and cUL Commercially Certified
- Stainless Steel Exterior
- Ruby Bearing
- Tungsten Carbide Shaft



PRECISION

Temperature Resolution	0.1°F/0.1°C
Temperature Stability	± 0.1°F/0.1°C
Maximum Water Temperature	194°F/90°C

USABILITY

Color TFT Touch Display	360° Adjustable Flow Direction
On-board Cooking Guide Sous Vide Toolbox™	Coil-less Heating Chamber
Manual Time & Temperature Controls	Low Water Detection
Integrated Digital Probe	Magnetic Impeller Coupling
Variable Flow Speed	Adjustable & Detachable Clamp

CONNECTIVITY

Bluetooth

WEIGHTS & DIMENSIONS

Unit Weight	4.4lb / 2kg
Unit Dimensions (L x D x H)	14.6in x 3.7in x 6.7in / 37.1cm x 9.3 x 17cm
Shipping Weight	7.1lb / 3.2kg
Shipping Dimensions (L x D x H)	16.3in x 5.8in x 9.9in / 41.5cm x 14.7cm x 25.2cm
SKU Number	CSV750PSS1BUC1

ACCESSORIES

- Adjustable & Detachable Clamp
- Magnetic Impeller
- 360° Adjustable Flow Direction Foot
- Digital Probe & Calibration Holder
- Carry Case with Handle.