

We put space to work.

Job ____

MetroMax 4 Drying Racks combine the corrosion protection and strength of MetroMax 4 with the convenience of a drying rack unit that efficiently sorts and holds pots, pans and trays while they dry to prevent wet nesting.

Three Tier Tray Rack:

36" (914mm) and 48" (1219mm) lengths. Each consists of (3) MetroMax 4 shelf frames, (4) 63" (1600mm) mobile posts, (4) corrosion resistant polymer horn casters (two swivel, two brake), (3) tray racks,

Four Tier Bulk Drying and Tray Rack:

36" (914mm) and 48" (1219mm) lengths. Each consists of (3) MetroMax 4 shelf frames, (1) MetroMax 4 shelf, (4) 63" (1600mm) mobile posts, (4) corrosion resistant polymer horn casters (two swivel, two brake), (2) stainless steel drop-in racks, (1) tray rack.

Four Tier Tray and Steam Pan Rack:

36" (914mm) and 48" (1219mm) lengths. Each consists of (4) MetroMax 4 shelf frames, (4) 63" (1600mm) mobile posts, (4) corrosion resistant polymer horn casters (two swivel, two brake), (2) tray racks, (2) steam pan racks.

Key Benefits

- **Promotes food safety** by preventing wet nesting, where two wet/damp items are nested together preventing proper airflow.
- **Superior air circulation:** Fast drying of trays, cutting boards, pans, lids, pots and all sink items.
- "Hold strong" slots: Tray and Pan Racks have tall slots to assure trays, cutting boards, steam pans, and other tall items don't tip over while being loaded/unloaded and during use.
- Wobble Free, Worry Free mobility: Sturdy carts are easy to maneuver with swivel polymer casters.
- Easy to Clean: Shelf mats, posts and epoxy coated drying racks have built-in Microban antimicrobial product protection. It keeps the product "cleaner between cleanings".
- Superior Organization: Optional hanging rails and grids help sort and dry utensils and other vessels with long handles.
- **NSF Listed**







MAX4-PR48VX3



MAX4-PR48VX4



Inhibits the growth of stain and odor causing bacteria.

Microban® does not protect users from food borne illness.

Normal cleaning practices should be maintained. Microban is a registered trademark of Microban Products Company.

All Metro Catalog Sheets are available on our website: www.metro.com



InterMetro Industries Corporation

LO2-231 Printed in U.S.A.





Specifications - Shelving Units, Drop-Ins, Tray Racks, Pan Racks

- Longitudinal Beams & Posts: Pultrusions continuous glass fibers and thermo set resin composite with built-in Microban antimicrobial product protection. Exterior surfaces are high-impact thermoplastic resin.
- End Beams, Adjustable Foot & Socket: Injection molded polyester thermoplastic resin with glass reinforcement.
- **Drop In Rack** -Electro-Polished Type 304 Stainless Steel
- Cutting Board/Tray Drying Rack: Corrosion resistant taupe epoxy coated steel with built-in Microban product protection and rigid PVC (non phtalate) extrusions.
- Shelf Mats: Polypropylene. Mats contain Microban antimicrobial product protection.
- Load Capacity: 200 lbs. (91kg) per drop-in rack, tray rack, or pan rack.

- Stationary Load Capacity: 2000lbs. (907kg)
- Mobile Load Capacity: 750 lbs. (340kg) per unit
- Polymer Casters: 2 swivel, 2 swivel with brakes. Corrosion-resistant, polymer horn, stainless steel axle and hardware. 5" (127mm) diameter.



MAX4-PR36VX2

Dimensions

MetroMax 4 Mobile Drying Rack Units

Three Tray Racks (three tier unit)

Model No.	Nominal Width (in.) (mm)	Nominal Length (in.) (mm)	Nominal Height (in.) (mm)	Approx. Pkd. Wt. (lbs.) (kg)	
MAX4-PR36VX2	24 610	36 914	68 1702	72.7 33.0	
MAX4-PR48VX2	24 610	48 1219	68 1702	86.9 39.4	

Two SS Drop-ins, One Tray Rack, One Bulk Shelf (4-tier)

Model No.	Nominal Width (in.) (mm)	Nominal Length (in.) (mm)	Nominal Height (in.) (mm)	Approx. Pkd. Wt. (lbs.) (kg)	
MAX4-PR36VX3	24 610	36 914	68 1702	65.0 29.5	
MAX4-PR48VX3	24 610	48 1219	68 1702	76.8 34.8	

Two Tray Racks and Two Pan Racks (4-tier)

	•				,	,				
	Model No.	Nomin (in.)	al Width (mm)	Nomina (in.)	Nominal Length (in.) (mm)		inal Height (mm)	Approx. Pkd. Wt. (lbs.) (kg)		
ĺ	MAX4-PR36VX4	24	610	36	914	(in.) 68	1702	80.6	,	
	MAX4-PR48VX4	24	610	48	1219	68	1702	95.3	43.2	

Note: For the actual dimensions for mobile units, add 2" (51mm) to the nominal dimension to account for the bumpers.



MAX4-PR36VX3



MAX4-PR36VX4