

# MIRRA 250 PLUS - 10"





- High-quality, stylish, lightweight and compact space saving design
- · Great cutting capacity in a compact footprint
- · Easy to carry for catering needs
- · Fan-cooled motor to avoid overheating
- Permanent blade ring guard for safe and easy sanitation
- · Safety hand guard mounted to the carriage
- The easy, fast breakdown and the increased blade and machine body gap makes cleaning a breeze

### **Features**

## Technical:

- The slide shaft is made of ground, chromed steel for a smoother operation.
- The high-quality bushings and ball bearings are self-lubricating.
- The dial thickness control cam system allows for an always precise cut.

#### Safety:

- A safety cover is placed under the motor and the electrical components.
- The hopper features an exclusive heavy duty plastic protection to keep operator's hand at a safe distance from the blade while operating the slicer.

#### Sannary:

- Easy to clean aluminum alloy construction does not crack or stain.
- The carriage and the blade cover are quickly removable without tools.

## Specifications

**Operation:** Gravity feed.

**Construction:** Polished, anodized aluminum alloy.

**Knife:** One piece, chromium plated 100Cr6 forged carbon steel blade.

**Sharpener:** Built-in, removable two stone dual action.

Slice thickness: Infinitely variable up to 1/2"

Motor 250 PLUS: 0.25 Hp (185W), belt-driven, fan-cooled.

Motor 300 PLUS: 0.33 Hp (245W), up to 0.5 Hp peak, belt-driven, fan-cooled.

**Electrical 250 PLUS:** 120V AC, 60Hz, 1.55A **Electrical 300 PLUS:** 120V AC, 60Hz, 1.8A

Plug & Cord: Attached, flexible, 3 wire SJT AWG 16, 6'4" long.

**Switch:** ON/OFF lighted rocker switch





Phone: +1 847-288-9500 Toll free: 866-643-6872




Certified to UL Standard 763 and NSF Standard 08 Certified to CSA Standard C22.2









	Ø Blade	Motor	Cut thickness	Blade rpm	Carriage stroke	Норрег	А	В	С	D	E	F	G	Х	Υ	Н	W	Net weight	Shipping	Gross weight
	mm/inch	watt/Hp	inch.	rpm	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	lbs.	inch.	lbs.
Mirra 250 PLUS	250/10"	185-0,25	1/2"	335	9 5/8"	9 <sup>1/16</sup> " x 9 <sup>1/16</sup> "	15 9/16"	9 5/8"	19 11/16"	22 1/16"	14 9/16"	22 7/16"	18 11/16"	8 7/16"	5 11/16"	7 1/16"	6 11/16"	35	23 <sup>5/8</sup> " x 19 <sup>11/16</sup> " x 16 <sup>9/16</sup> "	40
Mirra 300 PLUS	300/12"	245-0,33 - 0.5 peak	1/2"	350	11 1/4"	9 <sup>13/16</sup> " x 10 <sup>13/16</sup> "	171/8"	11 5/8"	23 5/8"	24	16 9/16"	25 3/16"	20 1/16"	9 13/16"	7 5/16"	8 7/8"	8 1/4"	45	31 <sup>1/2</sup> " x 23 <sup>5/8</sup> " x 20 <sup>1/2</sup> "	63