



COLUMN REFRIGERATION
Wine Reserve



Shown with optional stainless steel door overlay panel.



Shown with convertible shelf in display mode.

JOB	
AREA	
ITEM NO.	
MODEL NO.	

MODELS	DESCRIPTION
CC24W	Single Zone - Wine Column, Glass Door
CC24D	Dual Zone - Wine Column, Glass Door

KEY PRODUCT FEATURES AND BENEFITS

- CC24D Features patented dual zone technology for storage of red and white wine at optimal serving temperatures
- Smart Humidity advanced technology monitors humidity levels in the cabinet and pushes additional moisture into the cabinet to maintain 60-70% humidity maintaining corks and prevent oxidation
- Carbon air filtration removes odors from the cabinet that could be absorbed into corks over time
- PerliQ™ touch screen control panel disappears into the background until awoken for a modern look
- Customize temperature, activate sabbath mode, or adjust lighting with the sleek PerliQ™ Control panel – Smart temperature settings for red and white wine.
- All stainless steel and glass interior provides a hygienic, easy to clean, and beautiful cabinet
- Energy efficient and eco-friendly R600a refrigerant has zero ozone depletion potential and is up to 30% more efficient than systems using R134a

Quick Features:

- Triple-pane, UV-resistant glass provides protection from harmful light oxidation
- Convertible display shelf showcases 6 prized wine bottles and easily lays flat to store 11 bottles without additional parts and pieces
- Roll-on theatre lighting brightly illuminates cabinet, adjust brightness with 5 built in settings
- Blue and White LED Interior lighting; Slow fade on and off; Lighting brightness control displays intensity settings in 20% increments (20-40-60-80-100%)
- High capacity storage up to 99 750ml bottles
- Integrated design comes ready to accept custom panel and hardware, stainless steel panels available (ordered seperately)
- Full one year warranty and five year compressor warranty

Form No. Z2458
Rev 05.23.2021



COLUMN REFRIGERATION
Wine Reserve

SPECIFICATIONS		SINGLE ZONE	DUAL ZONE
NUMBER OF DOORS		1	1
EXTERIOR CABINET DIMENSIONS	Length - in. (mm)	23-3/4" (603)	23-3/4" (603)
	Depth - in. (mm) w/o overlay panel	24-1/16* (611)	24-1/6** (611)
	Height - in. (mm)	84" (2134)	84" (2134)
INTERIOR CABINET DIMENSIONS	Length - in. (mm)	19-3/4" (502)	19-3/4" (502)
	Depth - in. (mm)	18" (457)	18" (457)
	Height - in. (mm)	61-1/8" (1552)	61-1/8" (1552)
INTERNAL VOLUME Net. Cu. Ft. (Litres)		12.6 (357)	12.2 (345)
PRODUCT CAPACITY 750ml bottles	8 bottles on 11 fixed shelves 6 bottles on 1 display shelf	11-1	10-1
		94	86
SHIPPING WEIGHT Lbs. (kg.)		534	541
ELECTRICAL SPECIFICATIONS	Electrical Supply	115/60Hz/1PH	115/60Hz/1PH
	Running Load Amps	2.6	2.6
	Electrical Connection	Cord Connected NEMA 5-15P	Cord Connected NEMA 5-15P
	Defrost Type	Off Cycle	Off Cycle
	Lighting Type	LED	LED
REFRIGERANT	R600a Isobutane	53 grams	53 grams
	Temperature Range (F)	40° - 68° F	40° - 68° F**
ACCESSORIES	36" Two Tone Polished Chrome and Stainless Steel handle		
	Field Installed Stainless Steel overlay for glass door (Left or Right hinged) w/ lock		
	Stainless Steel Finish Panel for Left or Right Side		

*Without overlay panel

**Dual Zone Wine Upper compartment temperature setpoint must always be set at or above the lower compartment setpoint.

Perlick® COLUMN REFRIGERATION
Wine Reserve

