accucold

PTHC65G



36" x 23.63" x 23.5" (H x W x D)

Single chamber passive heating blanket warmer with glass door, stainless steel interior, digital thermostat, and lock

Highlights:

Designed and assembled in the USA

No internal fans or moving parts ensure silent, safe, and efficient operation

Stainless steel interior for durable use and easy cleaning

Product Features:

| 90 to 140°F temperature range | Designed and set to keep blankets warm in hospitals, medical and physical therapy offices, spas, and other facilities | |
|---------------------------------|--|--|
| Passive heating | Fixed heaters located at the bottom of the cabinet with no fans or moving parts to minimize lint buildup for safer, more efficient use | |
| Digital thermostat | Electronic controls are conveniently located externally for easy temperature adjustment | |
| Electronic readout | Large LED temperature display ensures your staff can easily monitor the interior temperature | |
| Silent operation | No moving parts to ensure a quiet performance | |
| Double pane tempered glass door | Heat-safe glass door offers a full view of stored contents, with a stainless steel door trim to highlight the interior | |
| Professional handle | Stainless steel handle completes the professional look | |
| Stainless steel interior | Interior walls are constructed from stainless steel to ensure lasting durability and easy cleaning | |
| Cantilevered shelving system | Three easily adjustable chrome shelves to accommodate virtually any size | |

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com



accuceld

PTHC65G Specifications:

| Overview | | |
|-------------------------------|---------------------|--|
| Height of Cabinet | 36.0" (91 cm) | |
| Width | 23.63" (60 cm) | |
| Depth | 23.5" (60 cm) | |
| Depth with Handle | 25.38" (64 cm) | |
| Depth with door at 90° | 46.0" (117 cm) | |
| Capacity | 4.57 cu.ft. (129 L) | |
| Door | Glass | |
| Cabinet | Black | |
| US Electrical Safety | ETL | |
| Canadian Electrical Safety | ETL-C | |
| Amps | 5.5 | |
| Voltage/Frequency | 115 V AC/60 Hz | |
| Weight | 140.0 lbs. (64 kg) | |
| Shipping Weight | 145.0 lbs. (66 kg) | |
| Estimated Time to Ship | Next day shipping | |
| Parts & Labor Warranty | 1 Year | |
| Warming Cabinet | | |
| Door Swing | RHD | |
| Reversible | Yes | |
| Adjustable Shelves | Yes | |
| Shelf Type | Chrome | |
| Shelf Qty | 3 | |
| Thermostat Type | Digital | |
| Interior Height | 22.5" (57 cm) | |
| Interior Width | 19.38" (49 cm) | |
| Interior Depth | 17.38" (44 cm) | |
| Level Legs | 4 | |
| Dolly | Optional | |
| Temperature Range | 90 to 140ºF | |
| | | |



