



PRODUCT SPECIFICATION

POLYLITE Plastic Folding Table

Model #: Various tables in Banquet, Round,
Seminar sizes

Updated: January 2006

Table Tops

Table top is constructed of a one-piece, blow-molded plastic top secured to a steel frame. Top design features a 1¼ inch edge to accommodate skirting clips. The durable tabletop is waterproof, stain resistant, heat resistant and may be used occasionally for outdoor applications, without damage from sun or UV rays.

Table tops are supported by an independent steel frame (18 gauge) that extends the full length of the table. Additional top support is added by five perpendicular 14 gauge steel cross braces welded to frame. Tops are secured to frame with heavy-duty machine screws.

Standard table height is 29 inches. Adjustable heights (21" - 32") in one inch increments) also available for an additional charge.

Legs

Legs are pedestal "inverted C" style, constructed of 18 gauge by 1 inch diameter steel tubing, on rectangular tables, and 1 1/8 inch diameter, 14 gauge steel on round tables. The tubing is powder coat painted to match frame.. The horizontal crossbar is machine welded to the vertical supports. Vertical tubing rests on four easily replaceable, non-marking plastic caps.

Locking mechanism is a sliding collar "gravity lock" style, for easy set-up and teardown.

Load Bearing

Table has been tested to support loads of 1000 pounds of "evenly distributed" weight, with no evidence of breakage or permanent deflection of table top.

Warranty

Palmer Snyder warrants that all folding tables will be new and manufactured with quality materials and workmanship. Palmer Snyder further agrees to replace promptly any part or parts which by reason of defective material or workmanship shall fail under normal use for a period of five years from date of acceptance for all POLYLITE brand products. This warranty does not apply when product has been altered or tampered with in any way, or when subjected to negligence or abuse.