SUMMIT

SBC15NKCSS



34.25" x 15" x 22.5" (H x W x D)

15" wide, built-in, commercially listed kegerator, auto defrost with digital thermostat, front lock, sealed back, and complete stainless steel exterior

Highlights:

Designed for built-in installation under the counter

Listed to NSF-7 standards and meets UL 471 for commercial use

15" wide design makes it ideal for smaller residential and commercial settings

Product Features:

| 15" wide design | Slim-fit design complements smaller commercial and residential spaces | |
|------------------------------------|--|--|
| Commercially approved | ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings | |
| Built-in capability | Make the best use of space by installing your appliance under the counter; NOTE: if installing flush with wall or cabinets, unit will require an extra χ " of space due to the door design. For more information, see the user manual | |
| Versatile kegerator | 2.9 cu.ft. interior can accept a 1/6 (sixtel) barrel keg or a pony keg; compatible with beer, wine, coffee, or kombucha tap systems | |
| Automatic defrost | Reduced user maintenance with auto defrost operation | |
| Digital thermostat | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit | |
| Tap cool system | Keeps cold air flowing to the tower for consistently cold beer | |
| Stainless steel floor cover | Interior includes steel cover to protect the floor when loading kegs | |
| Top guard rail (ships unassembled) | Attractive chrome guard rail helps to reduce spills and neaten service | |

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

 \checkmark



SUMMIT

SBC15NKCSS Specifications:

| Overview | |
|----------------------------|-------------------|
| Height of Cabinet | 34.25" (87 cm) |
| Width | 15.0" (38 cm) |
| Width with Door Open | 15.25" (39 cm) |
| Depth | 22.5" (57 cm) |
| Depth with Handle | 24.5" (62 cm) |
| Depth with door at 90° | 36.5" (93 cm) |
| Capacity | 2.9 cu.ft. (82 L) |
| Defrost Type | Automatic |
| Door | Stainless Stee |
| Cabinet | Stainless Stee |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Energy Usage/Year | 280.0kWh/yea |
| Amps | 1.25 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 80.0 lbs. (36 kg |
| Shipping Weight | 88.0 lbs. (40 kg |
| Estimated Time to Ship | 3 to 5 days |
| Parts & Labor Warranty | 1 Yea |
| Compressor Warranty | 5 Years |
| Kegerator | |
| Door Swing | RHD |
| Reversible | Yes |
| Adjustable Shelves | Yes |
| Shelf Type | Chrome |
| Shelf Qty | 2 |
| Thermostat Type | Digita |
| Fan Type | Exterio |
| Refrigerant | R600a |
| Refrigerant Amount | 1.06 oz |
| High Side PSI | 150.0 |
| Low Side PSI | 50.0 |
| Inter Height | 26.75" (68 cm) |
| Interior Width | 11.75" (30 cm |
| Interior Depth | 17.5" (44 cm) |
| Compressor Step Height | 3.75" (10 cm) |
| Compressor Step Width | 11.75" (30 cm |
| | |

| Compressor Step Depth | 5.0" (13 cm) |
|-----------------------|--------------|
| Level Legs Qty | 4 |
| Wheel Qty | 4 |
| Temperature Range | 34º to 50º F |



