



Project _____
 Item # _____ Quantity _____
 Model # _____



Reconfigurable Double Induction Range

(Model Shown: SM-251-2CR)

Model #	Voltage	Peak Power	Plug Type
SM-251-2CR (US)	208-240	2500 x 2 W	NEMA 6-30P
SM-253-2CR (Int'l)	220-240	2500 x 2 W	Plug & receptacle to be supplied by the customer, based on country code

Description:

Spring USA's Reconfigurable Double Induction Range is a heating unit for product cooking. The range features a low-profile design, satin stainless steel body, integrated oversized pan support, and detachable control panel for built-in applications. Each range includes our exclusive SmartScan® technology with over/under voltage protection, pan size and pan type recognition, and large LED power/temp display.

Construction & Performance Features:

- Tempered, smoked black glass faceplate
- Rugged, 5 mm thick, easy to clean, tempered glass top
- 100% silicone rubber protective top seal
- Non-skid, non-scratch footing/base
- 7' power cord with plug
- Removable mesh air filter
- Simple, solid state controls
- Power ON/OFF heavy duty knob

- Power ON/Pan-Present indicator lights
- Two (2) functions - 'Cook' or 'Temp' mode
- 'Cook'/'Temp' mode touch pad control
- 'Cook'/'Temp' mode indicator lights
- Simple, knob-set thermostat control
- Lighted temperature indicator
- Power level 1-20 in 'Cook' mode
- Temperature range 110°F-400°F (43°C-204°C) in 'Temp' mode

Standard Warranty:

Spring USA Induction Ranges offer a one (1) year, overnight exchange warranty, from the date of invoice, against manufacturers defects. See SpringUSA.com for more details.

Agency Listings:

- ETL
- UL STD 197
- FCC
- CETL
- ETL-Sanitation to NSF-4



Mar 2018

Reconfigurable Double Induction Range

Available Accessories/Alternate Configurations:

- Induction-ready Cookware & Serving Vessels [Spring USA Catalog]
- AF-350 Under-Counter Air Filter System
- Built-In, High Power Induction Ranges
- Custom Tabletop Induction featuring SmartStone®
- Mobile & Custom Configurations [Contact Spring USA]
- Cooking Utensils [Spring USA Catalog]

Electric Requirements:

Model #	Voltage	Phase	Hertz	Watts	Amps	Plug
SM-251-2CR (US)	208-240	1	60	2500 x 2 W	10.4 x 2	NEMA 6-30P
SM-253-2CR (Int'l)	220-240	1	50-60	2500 x 2 W	10.4 x 2	Plug & receptacle to be supplied by the customer, based on country code

Key Dimensions:



Removable controls allow for (2) countertop configurations or built-in applications



Net Weight: 29.1 lb. (13.2 kg)



Project _____

Item # _____ Quantity _____

Model # _____

Reconfigurable Double Induction Range

Shipping Dimensions:

Single Unit Shipping Carton

Model #	Length	Width	Height	Weight
SM-251-2CR (US)	34.0"	18.0"	4.5"	36.0 lb.
SM-253-2CR (Int'l)	864 mm	457 mm	114 mm	16.3 kg

Notes & Conditions:

1. For optimum performance, allow 4" clearance from front and sides for good air circulation.
Proper ventilation must be provided at all times.
2. Actual range temperature may vary due to a number of variables, such as ambient temperature in the immediate surrounding area, content and volume of food being heated or cooked, and whether or not you are using a cover on the serving vessel.
3. This induction range requires use of ferrous metal, induction-ready cookware.
4. Spring USA Induction Servers and Induction Warmers/Ranges are designed to work together as a system. Optimal performance is achieved by using Spring USA components in conjunction with each other. As the first to offer such induction systems, Spring USA cannot warranty the performance of facsimile products offered by other companies.