accuc@ld

ACR45L



31.5" x 19.5" x 22.75" (H x W x D)

Pharmacy Series ADA compliant 20" wide built-in undercounter all-refrigerator for vaccine storage, frost-free with an internal fan, external digital controls and thermometer, and lock

Highlights:

Less than 32" high to allow installation under lower ADA compliant counters

Specially designed to meet current CDC/VFC vaccine refrigeration guidelines for convenient storage in pharmacies and other healthcare facilities

External temperature readout of the current and high/low temperatures

Product Features:

Vaccine refrigerator	Purpose-built to meet the recommendations of the CDC and VFC for reliable vaccine storage	
ADA compliant	Sized just under 32" high to allow installation under lower ADA compliant counters	
Built-in capable	Front-breathing system allows the unit to be installed under cabinets with minimum clearance	
Slim 20" width	Full 2.65 cu.ft. capacity inside conveniently slim footprint	
Commercially listed	ETL-S listed to ANSI-NSF-7 commercial standards	
External temperature readout	Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button	
Digital thermostat	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience	
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range	
Buffered temperature probe	Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines	





accuc@ld

ACR45L Specifications:

Overview			
Height of Cabinet	31.5" (80 cm)		
Width	19.5" (50 cm)		
Depth	22.75" (58 cm)		
Depth with Handle	23.63" (60 cm)		
Depth with door at 90°	41.0" (104 cm)		
Capacity	2.65 cu.ft. (75 L)		
Defrost Type	Frost-Free		
Door	White		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Amps	1.0		
Voltage/Frequency	115 V AC/60 Hz		
Weight	79.0 lbs. (36 kg)		
Shipping Weight	89.0 lbs. (40 kg)		
Estimated Time to Ship	Next day delivery		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
Refrigerator Features			
Door Swing	RHD		
Reversible	Yes		
Shelf Type	Wire		
Shelf Qty	3		
Adjustable Shelves	Yes		
Thermostat Type	Digital		
Fan Type	Interior and Exterior		
Refrigerant Type	R600a		
Refrigerant Amount	0.99oz.		
Refrigerant Amount High Side PSI	0.99oz. 270.0		
High Side PSI	270.0		
High Side PSI Low Side PSI	270.0 105.0		
High Side PSI Low Side PSI Level Legs Qty	270.0 105.0 4		
High Side PSI Low Side PSI Level Legs Qty Interior Light	270.0 105.0 4 Yes		
High Side PSI Low Side PSI Level Legs Qty Interior Light Temperature Range	270.0 105.0 4 Yes		

Interior Depth	16.13" (41 cm)
Compressor Step Height	3.5" (9 cm)
Compressor Step Width	19.5" (50 cm)
Compressor Step Depth	4.75" (12 cm)



