accucold

FS24LMED2



Product Features:

Reliable temperature stability Designed and engineered to store vaccines and other sensitive materials under stable temperature conditions Digital thermostat Electronic controls for more precise temperature management, with temperature readout and controls externally located for added convenience High/low temperature alarm Audible alarm sounds if the interior temperature rises or falls out of set range NIST calibrated temperature display Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button Thermometer probe is encased in a glycol-filled bottle to maintain temperature readings Buffered temperature probe closest to stored contents, as recommended by the CDC and VFC's guidelines Factory installed lock Keyed lock for convenient security, with two keys included Manual defrost Static cooling system for reduced temperature fluctuations Hospital grade cord and plug Secure three-pronged cord for added unit safety Unit comes with a factory installed probe hole for users to connect their own monitoring 3/8" access port equipment

ACCUCOLD DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799 21.75" x 18.5" x 17.63" (H x W x D)

Compact medical/scientific all-freezer with digital thermostat, NIST calibrated thermometer/alarm, and front lock

Highlights:

Specially designed and featured to meet the CDC and VFC's guidelines for safe vaccine storage

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Assembled in the USA from domestic and imported components

accucoldinfo@summitappliance.com

accucold

FS24LMED2 Specifications:

Overview	
Height of Cabinet	21.75" (55 cm)
Width	18.5" (47 cm)
Depth	17.63" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.4 cu.ft. (40 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.8
Weight	40.0 lbs. (18 kg)
Shipping Weight	65.0 lbs. (29 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
D	
Reversible	Factory Reversible
Reversible Interior Height	Factory Reversible14.38" (37 cm)
	•
Interior Height	14.38" (37 cm)
Interior Height Interior Width	14.38" (37 cm) 13.5" (34 cm)
Interior Height Interior Width Interior Depth	14.38" (37 cm) 13.5" (34 cm) 13.25" (34 cm)
Interior Height Interior Width Interior Depth Shelf Type	14.38" (37 cm) 13.5" (34 cm) 13.25" (34 cm) Wire
Interior Height Interior Width Interior Depth Shelf Type Shelf Qty	14.38" (37 cm) 13.5" (34 cm) 13.25" (34 cm) Wire 1
Interior Height Interior Width Interior Depth Shelf Type Shelf Qty Thermostat Type	14.38" (37 cm) 13.5" (34 cm) 13.25" (34 cm) Wire 1 Digital
Interior Height Interior Width Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type	14.38" (37 cm) 13.5" (34 cm) 13.25" (34 cm) Wire 1 Digital R134a
Interior Height Interior Width Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount	14.38" (37 cm) 13.5" (34 cm) 13.25" (34 cm) Wire 1 Digital R134a 1.5 oz.
Interior Height Interior Width Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI	14.38" (37 cm) 13.5" (34 cm) 13.25" (34 cm) Wire 1 Digital R134a 1.5 oz. 280.0
Interior Height Interior Width Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	14.38" (37 cm) 13.5" (34 cm) 13.25" (34 cm) Wire 1 Digital R134a 1.5 oz. 280.0 110.0
Interior Height Interior Width Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs	14.38" (37 cm) 13.5" (34 cm) 13.25" (34 cm) Wire 1 Digital R134a 1.5 oz. 280.0 110.0 2
Interior Height Interior Width Interior Depth Shelf Type Shelf Qty Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Level Legs Compressor Step Height	14.38" (37 cm) 13.5" (34 cm) 13.25" (34 cm) Wire 1 Digital R134a 1.5 oz. 280.0 110.0 2 8.5" (22 cm)

