

NOVA53PDC



46" x 60.75" x 27.25" (H x W x D)

61" wide fully assembled commercial dipping cabinet made in Europe with digital thermostat, sneezeguard, and light

Highlights:

Fully assembled dipping cabinet with durable polycarbonate sneezeguard and light

Digital thermostat for easy temperature control, with a wide range between -13 and 23°F to accommodate ice cream, gelato, and other frozen treats

Tub holder baskets for convenient ice cream storage

Product Features:

Commercially listed	UL-S listed to NSF-7 Standards for use in commercial establishments	
Digital thermostat	Electronic controls for precise temperature management	
Wide temperature range	Digital thermostat can be set between -13 and +23°F to accommodate a variety of frozen treats	
Sneezeguard	Durable polycarbonate sneezeguard is pre-installed	
Ice cream tub holders	Five epoxy coated wire baskets with plastic lids included to hold standard ice cream tubs in place	
Strong insulation	3" thick insulation helps to ensure items stay cold	
Casters	Heavy duty wheels for smooth mobility (ship unassembled)	
Sliding glass lid	Two tempered glass lids with roller glides glide smoothly for easy use	
Removable lock	A keyed lock is included for optional use	







NOVA53PDC Specifications:

Overview		
Height of Cabinet	46.0" (117 cm)	
Width	60.75" (154 cm)	
Depth	27.25" (69 cm)	
Capacity	16.6 cu.ft. (470 L)	
Defrost Type	Manual	
Door	Glass	
Cabinet	White	
US Electrical Safety	UL	
Canadian Electrical Safety	ULC	
Sanitation	UL-S	
Amps	4.2	
Voltage/Frequency	115 V AC/60 Hz	
Weight	190.0 lbs. (86 kg)	
Shipping Weight	200.0 lbs. (91 kg)	
Estimated Time to Ship	5 to 7 days	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
Freezer		
Door Swing	Sliding	
Interior Height	24.0" (61 cm)	
Interior Width	54.5" (138 cm)	
Interior Depth	21.0" (53 cm)	
Thermostat Type	Digital	
Refrigerant Type	R290a	
Refrigerant Amount	3.17 oz.	
High Side PSI	345.0	
Low Side PSI	140.0	
Wheels	4	
Compressor Step Height	9.75" (25 cm)	
Compressor Step Width	7.88" (20 cm)	
Compressor Step Depth	21.0" (53 cm)	
Temperature Range	-13 to 23°F	

