

SBC56GBICSSADA



32.25" x 23.38" x 23" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap beer dispenser with glass door, lock, and stainless steel wrapped cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24" spaces

Product Features:

| ADA compliant height | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters | |
|---------------------------------|---|--|
| Commercially approved | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings | |
| Built-in capable | Front-breathing design allows fully recessed installation under counters | |
| Complete tap kit | Includes a 5 lb. CO2 tank and regulator, dual tap draft arm, Sankey American tap, connection hardware, and cleaning kit | |
| Dual tap system | Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs | |
| Double pane tempered glass door | Heat resistant design provides clear view to promote impulse buys | |
| Stainless steel wrapped cabinet | Exterior features a wrapped stainless steel finish for lasting durability in busy commercial settings | |
| Professional handle | Curved towel bar style handle in brushed stainless steel | |
| Factory-installed lock | Keyed lock conveniently located towards the top of the door for added security (2 keys included) | |







SBC56GBICSSADA Specifications:

| Overview | | | |
|-------------------------------|--------------------|--|--|
| Height of Cabinet | 32.0" (81 cm) | | |
| Height to Hinge Cap | 32.25" (82 cm) | | |
| Width | 23.63" (60 cm) | | |
| Depth | 23.5" (60 cm) | | |
| Depth with Handle | 25.63" (65 cm) | | |
| Depth with door at 90° | 45.13" (115 cm) | | |
| Capacity | 5.5 cu.ft. (156 L) | | |
| Defrost Type | Automatic | | |
| Door | Glass | | |
| Cabinet | Stainless Steel | | |
| US Electrical Safety | ETL | | |
| Canadian Electrical Safety | ETL-C | | |
| Sanitation | ETL-S | | |
| Amps | 1.8 | | |
| Voltage/Frequency | 115 V AC/60 Hz | | |
| Weight | 110.0 lbs. (50 kg) | | |
| Shipping Weight | 120.0 lbs. (54 kg) | | |
| Parts & Labor Warranty | 1 Year | | |
| Compressor Warranty | 5 Years | | |
| Beer Dispenser | | | |
| Door Swing | RHD | | |
| Reversible | Factory Reversible | | |
| Height Adjustable | 47.5 | | |
| Tap Kit | Yes | | |
| Number of Taps | 2 | | |
| Thermostat Type | Dial | | |
| Interior Light | Yes | | |
| Fan Type | Exterior | | |
| Refrigerant | R600a | | |
| Refrigerant Amount | 0.67 oz. | | |
| High Side PSI | 124.0 | | |
| Low Side PSI | 30.0 | | |
| Inter Height | 26.25" (67 cm) | | |
| Interior Width | 20.75" (53 cm) | | |
| Interior Depth | 17.75" (45 cm) | | |
| Compressor Step Height | 6.0" (15 cm) | | |
| | 20.75" (52.5%) | | |
| Compressor Step Width | 20.75" (53 cm) | | |

| Compressor Step Depth | 5.0" (13 cm) |
|-----------------------|--------------|
| Temperature Range | 34° to 43°F |





