

VT65MLPRO



33.5" x 23.63" x 23.5" (H x W x D)

24" wide -25°C all-freezer for freestanding use, manual defrost with a lock and probe hole for user-installed monitoring equipment

Highlights:

- Factory installed access port allows users to install their own monitoring equipment
- 25° C operation for safe storage of temperature sensitive materials
- Ideal 24" footprint offers large capacity in a slim fit

Product Features:

Slim counter height dimensions	24" width with generous interior capacity
-25°C capable	Low temperature capability ideal for certain sensitive items
Manual defrost	Efficient performance with reliable temperature stability
Factory installed lock	Top-mounted keyed lock for convenient security
Access port	Pre-installed 3/8" probe hole included in the rear allows users to connect their own monitoring equipment
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Pull-out drawers	Clear baskets for convenient and separated storage
Adjustable thermostat	Manage the temperature with ease and accuracy
Magnetic door gasket	Quality door gaskets ensure a tight seal for energy savings and improved performance

VT65MLPRO Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.13" (117 cm)
Capacity	3.2 cu.ft. (91 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.3
Shipping Weight	102.0 lbs. (46 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	2
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	-20°C to -30°C

