

VT65MLPROADA



32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant 24" wide -25°C all-freezer for freestanding use, manual defrost with a lock and probe hole for user-installed monitoring equipment

Highlights:

32" height for use in ADA compliant settings

Factory installed access port allows users to install their own monitoring equipment

-25° C operation for safe storage of temperature sensitive materials

Product Features:

ADA compliant	32" height for use in ADA compliant settings
Factory installed lock	Top-mounted keyed lock for convenient security
Access port	Pre-installed 3/8" probe hole included in the rear allows users to connect their own monitoring equipment
-25°C capable	Low temperature capability ideal for certain sensitive items
Manual defrost	Efficient performance with reliable temperature stability
Pull-out drawers	Clear baskets for convenient and separated storage
Digital thermostat	Electronic controls located in the front kickplate for easy and intuitive temperature management
Magnetic door gasket	Quality door gaskets ensure a tight seal for energy savings and improved performance
Foamed-in-place cabinet	Designed to ensure a sufficiently insulated interior

VT65MLPROADA Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	24.25" (62 cm)
Depth with door at 90°	45.0" (114 cm)
Capacity	3.2 cu.ft. (91 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	104.0 lbs. (47 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Digital
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	-20°C to -30°C

