







Fair Good Better Best Superflor



Intended for use in medium to heavy traffic areas, Water Master® entrance mats have a raised crushproof waffle design that aggressively scrapes and cleans. A rubber-edged perimeter traps dirt and moisture for superior water and soil control while molded rubber "cleats" on the underside of the mat grip the underlying surface minimizing mat movement. Water Master® uses a stain and fade resistant fiber to keep colors sharp and the mat looking new.

Test	Test Description	*Results
ASTM D3884-01	Abrasion Resistance	-0.99 grams (3.1%)
ASTM D6540-00	Accelerated Soiling	Based on Visual Inspection 3.5 - Vacuum Rating 4.0 - Rating After Extraction
ASTM E648-03	Critical Radiant Flux	0.11 Watts/Cm ²
CPSC FF 1-70 (ASTM D-2859)	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass
-	Water Retention	Weight Gain = 47.7% (0.427 gals./yd²)

 $^{{}^*\}text{All testing of NoTrax}{}^*\text{ floor matting has been performed by an independent testing laboratory}.$

11/2014

Appearance Rating Key		
5	No change	
4	Slight change	
3	Noticeable change	
2	Considerable change	
1	Severe change	



- 26 oz. face weight
- Thickness: 3/8"
- Rubber underside cleat design resists mat slippage
- Stock Sizes: 3' x 5', 4' x 6'
- Recommended and approved product as part of the GreenTRAX™ program for "Green Cleaning" environments

