

# VICTORY<sup>®</sup>

## ULTRASPEC

PROJECT: \_\_\_\_\_  
 ITEM # \_\_\_\_\_ QTY: \_\_\_\_\_  
 MODEL # \_\_\_\_\_  
 AIA # \_\_\_\_\_ SIS # \_\_\_\_\_

**BLAST CHILLER/SHOCK REACH-IN FREEZER**

## BLAST CHILLER/SHOCK REACH-IN FREEZER

### VBCF5-45PU



#### CABINET CONSTRUCTION

- Stainless Steel Exterior And Interior
- Die-Formed Interior Floor Has Rounded Corners
- Central Drain For Easy Cleaning
- Anti-Condensation Perimeter Heating Around Door Opening
- Ergonomic Vertical Door Handle And Stainless Steel
- Snap In Place Magnetic Gaskets Self Closing Door With Hold Open Stop At 100°

#### FEATURES

- Soft And Hard, Timed Or Core Probe Blast Chilling
- Soft And Hard, Timed Or Core Probe Shock Freezing
- Automatic Recognition Of Core Probe
- Multi Point Sensor Temperature Display Button
- Core Probe Heater Button
- HACCP Alarm Display Button
- Pre-Cooling Cycle Button
- Adjustable Evaporator Fan Speed Button
- Timed Manual Defrost Button
- USB Data Recorder
- Infinity Mode Program With Adjustable Set Point
- Automatic Conservation Mode At End Of Cycle
- On Board Recipe Book With 68 Pre-Set Programs
- 99 Free Memory Positions For Custom Programs
- LCD Illuminated Temperature Display
- Real Time Clock
- One, High Precision Heated Multi Sensor Probe
- Adjustable Stainless Steel Feet

#### REFRIGERATION

- Refrigeration System Uses R404 Refrigerant
- Evaporator Fitted With A High Flow Rate Fan Insures Maximum Cooling Efficiency
- Indirect Air Flow Assures Highest Product Quality
- Manual Defrosting With Door Open On A Timed Cycle
- Blast Chilling (194°F to 37°F in 90 minutes) Or Shock Freezing (194°F to 0°F in 240 minutes) Cycles



- ▶ 3 Year Parts & Labor Warranty Plus An Additional 2 Year Compressor Warranty
- ▶ Exclusive 2 Year Warranty On Magnetic Door Gaskets



Please verify qualifying units by visiting:  
[www.energystar.gov/cfs](http://www.energystar.gov/cfs)

#### OPTIONS & ACCESSORIES

- UV Sterilization Lamp (must be added at time of order)
- Change Door Swing
- Rs 485 Connection For External Monitoring System
- Single Sensor Probes (up to 4 possible)
- Casters With Brakes


3779 Champion Blvd, Winston-Salem, NC 27105

ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com | VictoryRefrigeration.com

Rev. 9/2/21 Printed in U.S.A.

APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_



We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

CHARACTERISTICS		REFRIGERATION DATA		SHIPPING DETAILS	
Width, Overall (in.)	33.46"	Condensing Unit Size, HP	1 1/2	Height	37"
Depth, Overall (with handle)	29.92"	Refrigerant	R404	Width	37"
Height Overall (in.)	33.46"	Capacity (BTU/HR) (95°F/14°F)	7,226	Depth	32"
Width, Door Open 90°	59.45"	PAN COUNT & PERFORMANCE		Crated Weight	349 lbs
Door Opening (in.)	28.74" x 14.96"	Sheet Pan Capacity (18"X26")	5		
Wall Thickness (in)	2.36"	Steam Table Pan Capacity (12"X20")	5		
ELECTRICAL DATA		Chilling Capacity In 90 Min	45 lbs		
Cabinet Voltage	208-240/60/1	Freezing Capacity In 240 Min	30 lbs		
Total Amperes	6.6	Climate Class	5		
NEMA Plug	6-15P				

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com | VictoryRefrigeration.com

Rev. 9/2/21 Printed in U.S.A.

an Ali Group Company



The Spirit of Excellence