

PROJECT:		
ITEM #		. OTY:
MODEL #		
ΛΙΛ #	SIS #	

WORKTOP DRAWER FREEZER

VWFD36HC-2





CABINET CONSTRUCTION

- Stainless Steel Exterior (galvanized back & bottom)
- Aluminum Interior
- 4" High, Foamed-In-Place Backsplash
- One Piece, Snap-In Magnetic Drawer Gaskets
- 6" Casters
- 8' Cord And Plug (see electrical data for details)

FEATURES

- Full Electronic Control
- Stay-Open Drawer Feature For Easy Product Loading
- Low Profile Horizontal Drawer Handles
- Heavy-Duty Pan Supports Provided
- Drawers Accommodates 6" Deep Full Size Food Service Pans In Both Upper And Lower Drawers (pans not included)
- Telescoping Drawer Slides With Locking Mechanism

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- Rear Mounted Refrigeration System
- Adaptive Defrost For Reduced Energy Consumption And More Consistent Product Temperatures
- Epoxy Coated Evaporator Coil
- Freezer Capable Of Maintaining Product Temperature -10°F

- 3 Year Parts & Labor Warranty
- Plus An Additional 4 Year Compressor Warranty
- Exclusive 2 Year Warranty On Magnetic Drawer Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)

OPTIONS & ACCESSORIES

- Stainless Steel Interior
- Stainless Steel Back

• Secure-Temp[™] Technology

- Cutting BoardDrawer Locks
- - 6" Legs or 6" Seismic Legs
- Please verify qualifying units by visiting: www.energystar.gov/cfs
- Casters: 3", Roller Kit, Low Profile
- Remote Models* (6" legs only) (refrigerant must be specified at time of order, see note on back on page)


3779 Champion Blvd, Winston-Salem, NC 27105

ph: (888) 845-9800 | fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com

VICTORY WORKTOP DRAWER FREEZER

VWFD36HC-2



We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS		
Net Capacity (cubic ft.)	8.69	Cabinet Voltage	115/60/1	Height	49"	
Width, Overall (in.)	36″	Total Amperes	4.0	Width	38″	
Depth, Overall (with handle)	32 3/4″	NEMA Plug (8' cord)	5-15P	Depth	37″	
Height Overall (6" casters)	39 5/8"	REFRIGERATION DATA		Crated Weight	294 lbs	
Depth, Drawer Extended	48 3/4"	Condensing Unit Size, HP	1/2			
Drawer Opening (in.)	31 5/8" x 7 1/2" 31 5/8" x 11 1/8"	Refrigerant*	R-290	*NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified at time of order.		
No. Of Drawers	2	Capacity (BTU/HR) (100°F/20°F)	1865			
		Heat Rejection (BTU/HR)	2797.5			
		Charge (Ibs/grams)	0.165/75			

3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com

Rev. 10/26/21 Printed in U.S.A.

an Ali Group Company

