

# STAINLESS STEEL WETBATH TABLES WITH ENCLOSED BASE





ltem #:	Qty #:
Model #: _	
Project #:	
-	

## WB-5G-NAT-BS Shown

#### **FEATURES:**

15,000 BTU'S / 2 and 3 compartments 25,000 BTU'S / 4 and 5 compartments Single control knob with 3 settings Pilot indicator openings Dish shelf of stainless steel Stainless steel undershelf

Stainless steel supporting dish shelf with removable 3/8" thick poly cutting board - Ships K.D.

Wet Gas units are perfect for prepared food. It maintains food temperature with hot steam. Add 1-2" of water to the wet bath unit to achieve the correct amount of hot moisture.

#### **MATERIAL:**

**TOP:** 20 gauge #302 stainless steel with die stamped pan openings. (11.875" x 20.062")

**BODY:** 22 gauge #430 stainless steel **LEGS:** 18 gauge, #302 stainless steel with fully

adjustable stainless steel bullet foot

LINERS: 8" deep, 22 Gauge, #302 stainless steel

**CUTTING BOARD:** White Thermoplastic

CUTTING BOARD BRACKETS: 16 gauge,

#302 stainless steel

PLATE SHELF: 18 gauge, #302 stainless steel

#### GAS:

Available for Natural c or Bottled Gas

1/2" female NPT connection to regulator

Infinite Control knobs

Indicator lights

**Note:** External pressure regulator is required. 4" WC pressure in for Natural Gas and 10" WC pressure in for LP

Model #	Gas Type	Length	Width*	# of Wells	Approx. Weight	Approx. Cu. Ft.
WB-2G-NAT-BS	NATURAL GAS	A = 31-13/16"	30-5/8"	2	145 lbs.	28
WB-3G-NAT-BS	NATURAL GAS	B = 47-1/8"	30-5/8"	3	175 lbs.	41
WB-4G-NAT-BS	NATURAL GAS	C = 62-7/16"	30-5/8"	4	225 lbs.	55
WB-5G-NAT-BS	NATURAL GAS	D = 77-3/4"	30-5/8"	5	296 lbs.	67
WB-2G-LP-BS	BOTTLED GAS	A = 31-13/16"	30-5/8"	2	145 lbs.	28
WB-3G-LP-BS	BOTTLED GAS	B = 47-1/8"	30-5/8"	3	175 lbs.	41
WB-4G-LP-BS	BOTTLED GAS	C = 62-7/16"	30-5/8"	4	225 lbs.	55
WB-5G-LP-BS	BOTTLED GAS	D = 77-3/4"	30-5/8"	5	296 lbs.	67

#### \*Width Includes 8" Cutting Board

NOTE: Units are not designed to cook or heat frozen or refrigerated foods. Food placed in tables should already be hot, and the table will maintain the proper temperatures





### Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes: Email: smartfab@advancetabco.com or Fax: 631-586-2933

# **DIMENSIONS and SPECIFICATIONS**

TOL ± .125"

ALL DIMENSIONS ARE TYPICAL



